NSN 5935-00-240-9381

Connector Adapter - Page 1 of 2

Thread Class: 2a and 2a



View Online at https://aerobasegroup.com/nsn/5935-00-240-9381

Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape w/flange
Overall Length:
3.750 inches
Overall Height:
1.375 inches
Overall Width:
1.375 inches
Environmental Protection:
Pressure proof
Unthreaded Mounting Hole Diameter:
0.196 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.120 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.120 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
Mating End Quantity: 2
2
2 Contact Position Arrangement Style:
2 Contact Position Arrangement Style: N 1st mating end
Contact Position Arrangement Style: N 1st mating end Contact Removability:
Contact Position Arrangement Style: N 1st mating end Contact Removability: Removable all mating ends single contact grouping
Contact Position Arrangement Style: N 1st mating end Contact Removability: Removable all mating ends single contact grouping Shell Type:
Contact Position Arrangement Style: N 1st mating end Contact Removability: Removable all mating ends single contact grouping Shell Type: Solid
Contact Position Arrangement Style: N 1st mating end Contact Removability: Removable all mating ends single contact grouping Shell Type: Solid Connector Locking Method:
Contact Position Arrangement Style: N 1st mating end Contact Removability: Removable all mating ends single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded shell
Contact Position Arrangement Style: N 1st mating end Contact Removability: Removable all mating ends single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded shell Radio Frequency Type Contact Characteristic Impedance In Ohms:
Contact Position Arrangement Style: N 1st mating end Contact Removability: Removable all mating ends single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded shell Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 all mating ends single contact grouping
Contact Position Arrangement Style: N 1st mating end Contact Removability: Removable all mating ends single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded shell Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 all mating ends single contact grouping Thready Qty Per Inch (tpi):
Contact Position Arrangement Style: N 1st mating end Contact Removability: Removable all mating ends single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded shell Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 all mating ends single contact grouping Thready Qty Per Inch (tpi): 24 and 24
Contact Position Arrangement Style: N 1st mating end Contact Removability: Removable all mating ends single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded shell Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 all mating ends single contact grouping Thready Qty Per Inch (tpi): 24 and 24 Thread Size:
Contact Position Arrangement Style: N 1st mating end Contact Removability: Removable all mating ends single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded shell Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 all mating ends single contact grouping Thready Qty Per Inch (tpi): 24 and 24 Thread Size: 0.624 inches and 0.750 inches
Contact Position Arrangement Style: N 1st mating end Contact Removability: Removable all mating ends single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded shell Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 all mating ends single contact grouping Thready Qty Per Inch (tpi): 24 and 24 Thread Size: 0.624 inches and 0.750 inches Contact Material:

NSN 5935-00-240-9381 Connector Adapter - Page 2 of 2



Insert Material:
Plastic all mating ends
Shell Material:
Copper alloy
Shell Surface Treatment:
Silver
Included Contact Quantity:
1 2nd mating end single contact grouping
Included Contact Type:
Coaxial socket 1st mating end single contact grouping
Precious Material And Location:
Contact and body surfaces silver
Precious Material And Weight:
0.110 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Unef and unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0