

View Online at <https://aerobasegroup.com/nsn/5935-00-240-9397>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

0.875 inches

Overall Diameter:

0.675 inches

Environmental Protection:

Corrosion resistant and heat resistant and humidity resistant and solvent resistant and vibration resistant

Distance From Mounting Shoulder To Front Face:

0.425 inches

Threaded Device Type:

Mounting bushing

Mating End Quantity:

1

Contact Removability:

Removable single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

450.0 single mating end all contact groupings

Contact Maximum Frequency Rating:

10000.0 megahertz single mating end all contact groupings

Shell Type:

Solid

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end all contact groupings

Thread Size:

0.190 inches

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings and copper single mating end all contact groupings

Insert Material:

Plastic polytetrafluoroethylene single mating end

Terminal Type:

Crimp single mating end all contact groupings

Contact Material Specification:

Qq-b-626, comp 22, 1/2 h federal specification single material response single mating end all contact groupings

Shell Material:

Copper alloy

Shell Material Specification:

Qq-b-626, comp 22, 1/2 h federal specification single material response

Insert Material Specification:

Mil-p-19468 military specification single material response single mating end

Included Contact Quantity:

1 single mating end all contact groupings

Bushing Accommodation Hole Shape:

Round

Precious Material And Location:

Contact surface gold

Precious Material:

Gold

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-p-19468 spec.