NSN 5935-00-241-0344

Thread Class: 2a and 2a and 2a Thread Direction:

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-241-0344

Right-hand and right-hand and right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.000 inches **Overall Width:** 0.500 inches **Threaded Device Type:** Back shell and coupling facility and mounting bushing **Mating End Quantity: Contact Removability:** Nonremovable single mating end single contact grouping **Shell Type:** Solid **Connector Locking Method:** Externally threaded shell **Thread Length:** 0.250 inches Thready Qty Per Inch (tpi): 32 and 32 and 32 Thread Size: 0.375 inches and 0.375 inches and 0.375 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Silver single mating end single contact grouping **Insert Material:** Plastic single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Aluminum alloy **Included Contact Quantity:**

1 single mating end single contact grouping

Coaxial socket single mating end single contact grouping

Included Contact Type:

NSN 5935-00-241-0344

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.005 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Unef and unef and unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0