## NSN 5935-00-241-2073

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-241-2073 **Thread Class:** 2a **Thread Direction:** Right-hand **Overall Length:** 1.406 inches **Overall Height:** 1.000 inches **Overall Width:** 1.000 inches **Unthreaded Mounting Hole Diameter:** 0.125 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.719 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.719 inches **Cable Entrance Diameter:** 0.500 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Connector Locking Method:** Externally threaded shell Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.625 inches **Insert Material:** Plastic single mating end **Shell Material:** Copper alloy **Included Contact Quantity:** 

1 single mating end single contact grouping

**Included Contact Type:** 

Round socket single mating end single contact grouping

## NSN 5935-00-241-2073

Electrical Receptacle Connector - Page 2 of 2



Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0