## NSN 5935-00-241-2882

Plug-in Electronic Components Socket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-241-2882

Body Material:
Plastic
Body Style:
Top mount, press fit
Fabrication Method:
Molded
Tempurature Rating:
-65.0 degrees celsius and 150.0 degrees celsius
Terminal Length:
Between 0.286 inches and 0.348 inches
Overall Height:
Between 0.544 inches and 0.626 inches
Overall Diameter:
Between 0.390 inches and 0.410 inches
Mounting Hole Style:
Single mounting hole/slot
Contact Resistance In Ohms:
0.009
Specific Equipment Accommodated:
Semiconducto
Contact Maximum Current Rating In Amps:
Contact Maximum Current Rating in Amps.
1.0
1.0
1.0 Contact Material:
1.0  Contact Material:  Beryllium copper
1.0  Contact Material:  Beryllium copper  Contact Surface Treatment:
1.0  Contact Material: Beryllium copper  Contact Surface Treatment: Gold and silver
1.0  Contact Material: Beryllium copper  Contact Surface Treatment: Gold and silver  Accommodated Contact Quantity:
1.0  Contact Material:  Beryllium copper  Contact Surface Treatment:  Gold and silver  Accommodated Contact Quantity:  8
1.0  Contact Material: Beryllium copper  Contact Surface Treatment: Gold and silver  Accommodated Contact Quantity: 8  Polarization Type:
1.0  Contact Material: Beryllium copper  Contact Surface Treatment: Gold and silver  Accommodated Contact Quantity: 8  Polarization Type: Contact position
1.0  Contact Material: Beryllium copper  Contact Surface Treatment: Gold and silver  Accommodated Contact Quantity: 8  Polarization Type: Contact position  Projection Length Above Mounting Surface:
1.0  Contact Material: Beryllium copper  Contact Surface Treatment: Gold and silver  Accommodated Contact Quantity: 8  Polarization Type: Contact position  Projection Length Above Mounting Surface: 0.062 inches
1.0  Contact Material: Beryllium copper  Contact Surface Treatment: Gold and silver  Accommodated Contact Quantity: 8  Polarization Type: Contact position  Projection Length Above Mounting Surface: 0.062 inches  Mounting Method:
1.0  Contact Material: Beryllium copper  Contact Surface Treatment: Gold and silver  Accommodated Contact Quantity: 8  Polarization Type: Contact position  Projection Length Above Mounting Surface: 0.062 inches  Mounting Method: Press fit
1.0  Contact Material: Beryllium copper  Contact Surface Treatment: Gold and silver  Accommodated Contact Quantity: 8  Polarization Type: Contact position  Projection Length Above Mounting Surface: 0.062 inches  Mounting Method: Press fit  Mounting Type For Which Designed:
Contact Material: Beryllium copper Contact Surface Treatment: Gold and silver Accommodated Contact Quantity: 8 Polarization Type: Contact position Projection Length Above Mounting Surface: 0.062 inches Mounting Method: Press fit Mounting Type For Which Designed: Chassis
Contact Material: Beryllium copper Contact Surface Treatment: Gold and silver Accommodated Contact Quantity: 8 Polarization Type: Contact position Projection Length Above Mounting Surface: 0.062 inches Mounting Method: Press fit Mounting Type For Which Designed: Chassis Contact Position Arrangement Style:

**Precious Material And Weight:** 

0.008 gold grains, troy and 0.008 silver grains, troy

## NSN 5935-00-241-2882

Plug-in Electronic Components Socket - Page 2 of 2



Precious Material:
Gold and silver
Terminal Type And Quantity:
8 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A02300