

View Online at <https://aerobasegroup.com/nsn/5935-00-241-3391>

Body Style:

Straight edge type w/card guide

Overall Length:

3.606 inches

Overall Height:

Between 0.755 inches and 0.805 inches

Overall Width:

Between 0.524 inches and 0.546 inches

Environmental Protection:

Humidity resistant and shock proof and salt water resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

Between 0.118 inches and 0.138 inches

Distance Between Mounting Facility Centers:

Between 3.319 inches and 3.349 inches

Board Accommodated Length:

0.115 inches single board and 0.125 inches single board

Board Accommodated Width:

0.074 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Lk-b28 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1800.0 single mating end single contact grouping

Polarization Method:

Contact to contact polarizing keys

Connector Locking Method:

Friction

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Tab, solder lug single mating end single contact grouping

Included Contact Quantity:

29 single mating end single contact grouping

Included Contact Type:

Hermaphrodite single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.029 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.