

View Online at https://aerobasegroup.com/nsn/5935-00-241-3669

Body Material: Plastic Body Style: Pcb mount Fabrication Method: Molded Overall Height: 0.464 inches Overall Diameter: Between 0.393 inches and 0.403 inches Specific Equipment Accommodated: Semiconductor Contact Material: Beryllium copper Contact Surface Treatment: Cadmium Accommodated Contact Quantity: 6 Printed Circuit Board Hole Arrangement Style: Six hole dimension "a" 0.310 inch Projection Length Above Mounting Surface: Between 0.035 inches and 0.045 inches Mounting Method: Terminal Mounting Type For Which Designed: Printed circuit Contact Position Arrangement Style: Circular Terminal Type And Quantity: 6 pin Shelf Life: N/a Unit of Measure: Pomilitarization: No Fig:
Body Style: Pcb mount Fabrication Method: Molded Overall Height: 0.464 inches Overall Diameter: Between 0.393 inches and 0.403 inches Specific Equipment Accommodated: Semiconductor Contact Material: Beryllium copper Contact Surface Treatment: Cadmium Accommodated Contact Quantity: 6 Printed Circuit Board Hole Arrangement Style: Six hole dimension "a" 0.310 inch Projection Length Above Mounting Surface: Between 0.035 inches and 0.045 inches Mounting Method: Terminal Mounting Type For Which Designed: Printed circuit Contact Position Arrangement Style: Circular Terminal Type And Quantity: 6 pin Shelf Life: N/a Unit Of Measure: - Demilitarization: No
Peb mount Fabrication Method: Nolded Overall Height: 0.464 inches Overall Diameter: Between 0.393 inches and 0.403 inches Specific Equipment Accommodated: Semiconductor Contact Material: Beryllium copper Contact Surface Treatment: Cadmium Accommodated Contact Quantity: 6 Printed Circuit Board Hole Arrangement Style: Six hole dimension "a" 0.310 inch Projection Length Above Mounting Surface: Between 0.035 inches and 0.045 inches Mounting Method: Terminal Mounting Type For Which Designed: Circular Circular Scincular Signia Style: Circular
Fabrication Method:MoldedOverall Height:0.464 inchesOverall Diameter:Between 0.393 inches and 0.403 inchesSpecific Equipment Accommodated:SemiconductorContact Material:Beryllium copperContact Surface Treatment:CadmiumAccommodated Contact Quantity:6Printed Circuit Board Hole Arrangement Style:Six hole dimension "a" 0.310 inchProjection Length Above Mounting Surface:Between 0.035 inches and 0.045 inchesMounting Method:TerminalMounting Type For Which Designed:Printed circuitContact Position Arrangement Style:CircularTerminal Type And Quantity:6 pinShelf Life:N/aUnit Of Measure:-Demilitarization:No
Molded Overall Height: 0.464 inches Overall Diameter: Between 0.393 inches and 0.403 inches Specific Equipment Accommodated: Semiconductor Contact Material: Beryllium copper Contact Surface Treatment: Cadmium Accommodated Contact Quantity: 6 Printed Circuit Board Hole Arrangement Style: Six hole dimension "a" 0.310 inch Projection Length Above Mounting Surface: Between 0.035 inches and 0.045 inches Mounting Method: Terminal Mounting Type For Which Designed: Printed circuit Contact Position Arrangement Style: Circular Terminal Type And Quantity: 6 pin Shelf Life: N/a Unit Of Measure: Demilitarization: No
Overall Height:0.464 inchesOverall Diameter:Between 0.393 inches and 0.403 inchesSpecific Equipment Accommodated:SemiconductorContact Material:Beryllium copperContact Surface Treatment:CadmiumAccommodated Contact Quantity:6Printed Circuit Board Hole Arrangement Style:Six hole dimension "a" 0.310 inchProjection Length Above Mounting Surface:Between 0.035 inches and 0.045 inchesMounting Method:TerminalMounting Type For Which Designed:Printed circuitContact Position Arrangement Style:CircularBeheff Life:N/aUnit Of Measure:Demilitarization:No
0.464 inches Overall Diameter: Between 0.393 inches and 0.403 inches Specific Equipment Accommodated: Semiconductor Contact Material: Beryllium copper Contact Surface Treatment: Cadmium Accommodated Contact Quantity: 6 Printed Circuit Board Hole Arrangement Style: Six hole dimension "a" 0.310 inch Projection Length Above Mounting Surface: Between 0.035 inches and 0.045 inches Mounting Method: Terminal Mounting Type For Which Designed: Circular Circular Sheff Life: N/a Unit Of Measure: Demilitarization: No
Overall Diameter:Between 0.393 inches and 0.403 inchesSpecific Equipment Accommodated:SemiconductorContact Material:Beryllium copperContact Surface Treatment:CadmiumAccommodated Contact Quantity:6Printed Circuit Board Hole Arrangement Style:Six hole dimension "a" 0.310 inchProjection Length Above Mounting Surface:Between 0.035 inches and 0.045 inchesMounting Method:TerminalMounting Type For Which Designed:Printed circuitContact Position Arrangement Style:CircularShelf Life:N/aUnit Of Measure:Demilitarization:No
Between 0.393 inches and 0.403 inches Specific Equipment Accommodated: Semiconductor Contact Material: Beryllium copper Contact Surface Treatment: Cadmium Accommodated Contact Quantity: Cadmium Accommodated Contact Quantity: Cather Circuit Board Hole Arrangement Style: Six hole dimension "a" 0.310 inch Projection Length Above Mounting Surface: Between 0.035 inches and 0.045 inches Mounting Method: Terminal Mounting Type For Which Designed: Printed circuit Contact Position Arrangement Style: Circular Ferminal Type And Quantity: 6 pin Shelf Life: N/a Unit Of Measure: Demilitarization: No
Specific Equipment Accommodated: Semiconductor Contact Material: Beryllium copper Contact Surface Treatment: Cadmium Accommodated Contact Quantity: Accommodated Contact Quantity: Cadmium Accommodated Contact Quantity: 6 Printed Circuit Board Hole Arrangement Style: Six hole dimension "a" 0.310 inch Projection Length Above Mounting Surface: Between 0.035 inches and 0.045 inches Between 0.035 inches and 0.045 inches Mounting Method: Terminal Mounting Type For Which Designed: Printed circuit Contact Position Arrangement Style: Circular Ferminal Type And Quantity: 6 pin Shelf Life: N/a Unit Of Measure:
Semiconductor Contact Material: Beryllium copper Contact Surface Treatment: Cadmium Accommodated Contact Quantity: 6 Printed Circuit Board Hole Arrangement Style: Six hole dimension "a" 0.310 inch Projection Length Above Mounting Surface: Between 0.035 inches and 0.045 inches Mounting Method: Terminal Mounting Type For Which Designed: Printed circuit Contact Position Arrangement Style: Circular Terminal Type And Quantity: 6 pin Shelf Life: N/a Unit Of Measure: Demilitarization:
Contact Material: Beryllium copper Contact Surface Treatment: Cadmium Accommodated Contact Quantity: 6 Printed Circuit Board Hole Arrangement Style: Six hole dimension "a" 0.310 inch Projection Length Above Mounting Surface: Between 0.035 inches and 0.045 inches Mounting Method: Terminal Mounting Type For Which Designed: Printed circuit Contact Position Arrangement Style: Circular Terminal Type And Quantity: 6 pin Shelf Life: N/a Unit Of Measure: Demilitarization:
Beryllium copper Contact Surface Treatment: Cadmium Accommodated Contact Quantity: 6 Printed Circuit Board Hole Arrangement Style: Six hole dimension "a" 0.310 inch Projection Length Above Mounting Surface: Between 0.035 inches and 0.045 inches Hounting Method: Terminal Mounting Type For Which Designed: Printed circuit Contact Position Arrangement Style: Circular Terminal Type And Quantity: 6 pin Shelf Life: N/a Unit Of Measure: Demilitarization: No
Contact Surface Treatment: Cadmium Accommodated Contact Quantity: 6 Printed Circuit Board Hole Arrangement Style: Six hole dimension "a" 0.310 inch Projection Length Above Mounting Surface: Between 0.035 inches and 0.045 inches Mounting Method: Terminal Mounting Type For Which Designed: Printed circuit Contact Position Arrangement Style: Circular Terminal Type And Quantity: 6 pin Shelf Life: N/a Unit Of Measure: Demilitarization:
Cadmium Accommodated Contact Quantity: 6 Printed Circuit Board Hole Arrangement Style: Six hole dimension "a" 0.310 inch Projection Length Above Mounting Surface: Between 0.035 inches and 0.045 inches Between 0.035 inches and 0.045 inches Mounting Method: Terminal Mounting Type For Which Designed: Printed circuit Contact Position Arrangement Style: Circular Freminal Type And Quantity: 6 pin Shelf Life: N/a Unit Of Measure: Demilitarization: No
Accommodated Contact Quantity: 6 Printed Circuit Board Hole Arrangement Style: Six hole dimension "a" 0.310 inch Projection Length Above Mounting Surface: Between 0.035 inches and 0.045 inches Mounting Method: Terminal Mounting Type For Which Designed: Printed circuit Contact Position Arrangement Style: Circular Terminal Type And Quantity: 6 pin Shelf Life: N/a Unit Of Measure: Demilitarization: No
6 Printed Circuit Board Hole Arrangement Style: Six hole dimension "a" 0.310 inch Projection Length Above Mounting Surface: Between 0.035 inches and 0.045 inches Between 0.035 inches and 0.045 inches Mounting Method: Terminal Mounting Type For Which Designed: Printed circuit Contact Position Arrangement Style: Circular Terminal Type And Quantity: 6 pin Shelf Life: N/a Unit Of Measure: Demilitarization:
Printed Circuit Board Hole Arrangement Style: Six hole dimension "a" 0.310 inch Projection Length Above Mounting Surface: Between 0.035 inches and 0.045 inches Mounting Method: Terminal Mounting Type For Which Designed: Printed circuit Contact Position Arrangement Style: Circular Terminal Type And Quantity: 6 pin Shelf Life: N/a Unit Of Measure: Demilitarization: No
Six hole dimension "a" 0.310 inch Projection Length Above Mounting Surface: Between 0.035 inches and 0.045 inches Mounting Method: Terminal Mounting Type For Which Designed: Printed circuit Contact Position Arrangement Style: Circular Terminal Type And Quantity: 6 pin Shelf Life: N/a Unit Of Measure:
Projection Length Above Mounting Surface: Between 0.035 inches and 0.045 inches Mounting Method: Terminal Mounting Type For Which Designed: Printed circuit Contact Position Arrangement Style: Circular Circular Terminal Type And Quantity: 6 pin Shelf Life: N/a Unit Of Measure:
Between 0.035 inches and 0.045 inches Mounting Method: Terminal Mounting Type For Which Designed: Printed circuit Contact Position Arrangement Style: Circular Terminal Type And Quantity: 6 pin Shelf Life: N/a Unit Of Measure: Demilitarization: No
Mounting Method: Terminal Mounting Type For Which Designed: Printed circuit Contact Position Arrangement Style: Circular Terminal Type And Quantity: 6 pin Shelf Life: N/a Unit Of Measure: Demilitarization: No
Terminal Mounting Type For Which Designed: Printed circuit Contact Position Arrangement Style: Circular Terminal Type And Quantity: 6 pin Shelf Life: N/a Unit Of Measure: Demilitarization: No
Mounting Type For Which Designed: Printed circuit Contact Position Arrangement Style: Circular Terminal Type And Quantity: 6 pin Shelf Life: N/a Unit Of Measure: Demilitarization: No
Printed circuit Contact Position Arrangement Style: Circular Terminal Type And Quantity: 6 pin Shelf Life: N/a Unit Of Measure: Demilitarization: No
Contact Position Arrangement Style: Circular Terminal Type And Quantity: 6 pin Shelf Life: N/a Unit Of Measure: Demilitarization:
Circular Terminal Type And Quantity: 6 pin Shelf Life: N/a Unit Of Measure: Demilitarization: No
Terminal Type And Quantity: 6 pin Shelf Life: N/a Unit Of Measure: Demilitarization: No
6 pin Shelf Life: N/a Unit Of Measure: Demilitarization: No
Shelf Life: N/a Unit Of Measure: Demilitarization: No
N/a Unit Of Measure: Demilitarization: No
Unit Of Measure: Demilitarization: No
 Demilitarization: No
No
No
Fiig:
-
A02300