

View Online at <https://aerobasegroup.com/nsn/5935-00-241-7238>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

1.250 inches

**Overall Height:**

Between 1.156 inches and 1.219 inches

**Overall Width:**

Between 1.156 inches and 1.219 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.117 inches and 0.123 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

Between 0.901 inches and 0.911 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 0.901 inches and 0.911 inches

**Distance From Mounting Shoulder To Front Face:**

Between 0.562 inches and 0.578 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

14s-7 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

10.0 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Thread Length:**

0.375 inches

**Thready Qty Per Inch (tpi):**

20

**Thread Size:**

0.875 inches

**Terminal Location:**

Back single mating end single contact grouping

**Insert Material:**

Rubber single mating end

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Copper alloy

**Included Contact Quantity:**

3 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0