

View Online at <https://aerobasegroup.com/nsn/5935-00-241-9636>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Rectangular shape

Overall Length:

1.560 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.312 inches

Overall Height:

0.430 inches

Overall Width:

0.500 inches

Environmental Protection:

Corrosion resistant

Unthreaded Mounting Hole Diameter:

0.093 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.342 inches

Threaded Device Type:

Mounting stud

Mating End Quantity:

1

Contact Position Arrangement Style:

34 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Polarization Method:

Guide pin/socket

Thread Length:

0.190 inches

Thread Size:

0.086 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Qq-b-626, comp 360 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14, ty sdi-5 military specification single material response single mating end

Included Contact Quantity:

34 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.034 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.