NSN 5935-00-242-1968

Electrical Receptacle Connector - Page 1 of 2

Tab, solder lug single mating end single contact grouping



View Online at https://aerobasegroup.com/nsn/5935-00-242-1968 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, rectangular **Overall Width:** 2.670 inches **Environmental Protection:** Corrosion resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.136 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.765 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 2.282 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 90 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 8.5 single mating end single contact grouping **Polarization Method:** Guide pin/socket **Connector Locking Method:** Screw lock pin **Thread Size:** 0.112 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:**

NSN 5935-00-242-1968

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity: 90 single mating end single contact grouping **Included Contact Type:** Hermaphrodite single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.090 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** Demilitarization:

No Fiig: A039b0