

View Online at <https://aerobasegroup.com/nsn/5935-00-242-1968>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, rectangular

**Overall Width:**

2.670 inches

**Environmental Protection:**

Corrosion resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:**

0.136 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

0.765 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

2.282 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

90 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

8.5 single mating end single contact grouping

**Polarization Method:**

Guide pin/socket

**Connector Locking Method:**

Screw lock pin

**Thread Size:**

0.112 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Terminal Type:**

Tab, solder lug single mating end single contact grouping

**Included Contact Quantity:**

90 single mating end single contact grouping

**Included Contact Type:**

Hermaphrodite single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.090 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0