NSN 5935-00-242-2367

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-242-2367 **Body Style:** Straight shape, external coupling w/backshell **Overall Length:** 1.281 inches **Overall Height:** 0.828 inches **Overall Width:** 0.828 inches **Environmental Protection:** Moisture resistant and salt water resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.115 inches and 0.125 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.594 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.594 inches **Distance From Mounting Shoulder To Front Face:** Between 0.431 inches and 0.462 inches **Mating End Quantity: Contact Position Arrangement Style:** 8-33 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 600.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: **Connector Locking Method:** Bayonet pin **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

NSN 5935-00-242-2367

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium
ncluded Contact Quantity:
3 single mating end single contact grouping
ncluded Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.015 gold grains, troy
Precious Material:
Gold
Test Data Document:
31349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
31349-mil-c-26482 government specification
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Filg:
A039b0