NSN 5935-00-242-4523

Telephone Jack - Page 1 of 2

Test Data Document:



View Online at https://aerobasegroup.com/nsn/5935-00-242-4523 **Thread Class:** 2a **Thread Direction:** Right-hand **Electrical Insulation Feature:** Insulated completely **Body Style:** Right angle threaded bushing mounted short frame **Overall Length:** 1.687 inches **Overall Height:** 1.750 inches **Overall Width:** 0.750 inches **Mounting Bushing Length:** 0.375 inches **Bushing Accommodation Hole Shape:** Round **Accommodated Finger Type:** Two conductor, round tip single finger **Finger Accommodation Diameter:** 0.252 inches single finger **Finger Accommodation Length:** 1.015 inches single finger **Bushing Thru-hole Accommodation Diameter:** 0.375 inches **Jack Contact Arrangement Designator: Mounting Facility Type And Quantity:** 1 bushing **Thread Size:** 0.375 inches **Terminal Type:** Tab, solder lug Material: Any acceptable terminal **Surface Treatment:** Tin terminal **Surface Treatment:** Any acceptable contact

81349-mil-j-641 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

NSN 5935-00-242-4523 Telephone Jack - Page 2 of 2



Thread Series Designator:
Unef
Specification Data:
81349-mil-j-641 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A03400