Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-243-0414

Body Style: Straight shape, external coupling **Overall Length:** Between 1.078 inches and 1.140 inches **Overall Height:** Between 1.766 inches and 1.796 inches **Overall Width:** Between 1.766 inches and 1.796 inches **Environmental Protection:** Pressure proof and moisture resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.115 inches and 0.125 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 1.432 inches and 1.442 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 1.432 inches and 1.442 inches **Distance From Mounting Shoulder To Front Face:** Between 0.516 inches and 0.546 inches Mating End Quantity: 1 **Contact Position Arrangement Style:** 61 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway Shell Type: Solid

Connector Locking Method:

Spring friction

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic silicone mineral filled single mating end

Terminal Type:

Crimp single mating end single contact grouping



Shell Material: Aluminum alloy Shell Surface Treatment: Cadmium and chromate **Included Contact Quantity:** 61 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.061 gold grains, troy **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0