## NSN 5935-00-243-1866

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-243-1866 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.175 inches **Overall Height:** 2.510 inches **Overall Width:** 2.510 inches **Unthreaded Mounting Hole Diameter:** Between 0.168 inches and 0.183 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 1.933 inches and 1.943 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:** Between 1.933 inches and 1.943 inches **Distance From Mounting Shoulder To Front Face:** Between 0.890 inches and 0.906 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 36-10 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 22.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type:

Solid

**Connector Locking Method:** 

Externally threaded shell

## NSN 5935-00-243-1866

Electrical Receptacle Connector - Page 2 of 2



| Thread Length:   |
|--|
| 0.630 inches   |
| Thready Qty Per Inch (tpi):                            |
| 16   |
| Thread Size:   |
| 2.250 inches   |
| Terminal Location:                                     |
| Back single mating end single contact grouping         |
| Contact Material:                                      |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment:                             |
| Silver single mating end single contact grouping       |
| Insert Material:                                       |
| Rubber single mating end                               |
| Terminal Type:   |
| Crimp single mating end single contact grouping        |
| Shell Material:  |
| Aluminum alloy   |
| Shell Surface Treatment:                               |
| Cadmium and chromate                                   |
| Included Contact Quantity:                             |
| 48 single mating end single contact grouping           |
| Included Contact Type:                                 |
| Round socket single mating end single contact grouping |
| Precious Material And Location:                        |
| Contact surfaces silver                                |
| Precious Material And Weight:                          |
| 0.048 silver grains, troy                              |
| Precious Material:                                     |
| Silver   |
| Thread Series Designator:                              |
| Un   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:                                       |
|  |
| Demilitarization:                                      |
| No   |
| Fiig:  |
| A039b0   |