View Online at https://aerobasegroup.com/nsn/5935-00-243-4083

Electrical Receptacle Connector - Page 1 of 2 **Body Style:** Straight shape **Overall Length:** Between 3.204 inches and 3.234 inches **Overall Height:** 0.609 inches **Overall Width:** Between 0.423 inches and 0.453 inches **Unthreaded Mounting Hole Diameter:** 0.138 inches **Distance Between Mounting Facility Centers:** Between 2.805 inches and 2.819 inches Mating End Quantity: 1 **Contact Position Arrangement Style:** 17 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Solder well single mating end single contact grouping **Contact Material Specification:** Qq-b-750 federal specification single material response single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:**

Cadmium and chromate

Shell Material Specification:

Qq-a-591 federal specification single material response

NSN 5935-00-243-4083

Electrical Receptacle Connector - Page 2 of 2



Insert Material Specification: Mil-m-14, type mdg military specification single material response single mating end **Included Contact Quantity:** 17 single mating end single contact grouping Included Contact Type: Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.017 gold grains, troy **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-m-14 spec.