## NSN 5935-00-243-5770

Electrical Receptacle Connector Body - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-243-5770 **Thread Class:** 2a and 2b and 2a **Thread Direction:** Right-hand and right-hand and right-hand **Body Style:** Straight shape **Overall Length:** Between 0.775 inches and 0.785 inches **Overall Height:** 0.650 inches **Overall Width:** Between 0.185 inches and 0.195 inches **Environmental Protection:** Moisture resistant and salt water resistant and vibration resistant and weatherproof **Distance Between Mounting Facility Centers:** Between 0.557 inches and 0.567 inches **Threaded Device Type:** Coupling facility and mounting stud **Mating End Quantity:** 12 **Contact Position Arrangement Style:** 7 single mating end **Polarization Method:** Jackscrew and polarization boss **Connector Locking Method:** Jackscrew-socket **Thread Size:** 0.086 inches and 0.086 inches and 0.086 inches **Insert Material:** Plastic diallyl phthalate glass filled single mating end or plastic epoxy single mating end or plastic phenolic single mating end **Insert Material Specification:** Mil-p-19833, type gdi-30f military specification single material response single mating end **Thread Series Designator:** Unc and unc and unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig:

A039b0

## NSN 5935-00-243-5770

Electrical Receptacle Connector Body - Page 2 of 2



Mil-std (military Standard):

Mil-p-19833 spec.