

View Online at https://aerobasegroup.com/nsn/5935-00-243-8078

| т | Fhread Class: |
|---|--------------------------------------------------------------------------------------|
| | |
| | ra Thread Direction: |
| - | |
| | Right-hand |
| | Body Style: |
| | Straight shape, rectangular |
| | Overall Length: |
| | Between 1.710 inches and 1.770 inches |
| | Overall Height: |
| | Between 1.850 inches and 1.870 inches |
| - | Overall Width: |
| | Between 2.865 inches and 2.885 inches |
| | Environmental Protection: |
| | Thermal shock resistant |
| | Jnthreaded Mounting Hole Diameter: |
| - | 0.149 inches |
| | Center To Center Distance Between Mounting Facilities Parallel To Height: |
| | Between 1.240 inches and 1.260 inches |
| | Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| | Between 2.490 inches and 2.510 inches |
| | Threaded Device Type: |
| | Coupling facility |
| N | Nating End Quantity: |
| 1 | |
| | Contact Position Arrangement Style: |
| | 58 single mating end |
| P | Polarization Method: |
| | Polarization boss |
| | Connector Locking Method: |
| J | lackscrew |
| C | Operating Tempurature Rating: |
| B | Between -54.0 degrees celsius and 125.0 degrees celsius |
| Т | Fhready Qty Per Inch (tpi): |
| 2 | 28 |
| Т | Fhread Size: |
| 0 | 0.250 inches |
| h | nsert Material: |
| F | Plastic diallyl phthalate glass filled single mating end |
| h | nsert Material Specification: |
| N | Iil-m-14, ty sdg-f military specification single material response single mating end |
| Т | Thread Series Designator: |
| ι | Jnf |

Electrical Receptacle Connector Body - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.