

View Online at <https://aerobasegroup.com/nsn/5935-00-243-8292>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape w/flange

Overall Length:

Between 1.980 inches and 2.000 inches

Overall Height:

Between 0.990 inches and 1.010 inches

Overall Width:

Between 0.990 inches and 1.010 inches

Environmental Protection:

Pressure proof and heat resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

Between 0.120 inches and 0.130 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.713 inches and 0.723 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.713 inches and 0.723 inches

Distance From Mounting Shoulder To Front Face:

Between 1.240 inches and 1.260 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

2

Contact Position Arrangement Style:

N all mating ends

Contact Removability:

Nonremovable all mating ends single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 all mating ends single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends single contact grouping

Thread Size:

0.625 inches

Contact Material:

Copper alloy all mating ends single contact grouping

Contact Surface Treatment:

Gold all mating ends single contact grouping

Insert Material:

Plastic tetrafluoroethylene all mating ends

Shell Material:

Steel comp 305

Shell Material Specification:

Qq-s-763, class 305 federal specification single material response

Included Contact Quantity:

1 all mating ends single contact grouping

Included Contact Type:

Coaxial socket all mating ends single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.010 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0