

View Online at https://aerobasegroup.com/nsn/5935-00-244-8015

| Thread Class: |
|---|
| 2a and 2b and 2a |
| Thread Direction: |
| Right-hand and right-hand and right-hand |
| Body Style: |
| Straight shape |
| Overall Length: |
| 2.906 inches |
| Overall Height: |
| 0.890 inches |
| Overall Width: |
| 1.768 inches |
| Environmental Protection: |
| Moisture resistant and salt water resistant and vibration proof |
| Distance Between Mounting Facility Centers: |
| 2.375 inches |
| Threaded Device Type: |
| Coupling facility and mounting stud |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 25-104 single mating end |
| Polarization Method: |
| Jackscrew and shell |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Jackscrew-socket |
| Thread Length: |
| 0.234 inches |
| Thready Qty Per Inch (tpi): |
| 32 and 32 and 40 |
| Thread Size: |
| 0.138 inches and 0.138 inches and 0.112 inches |
| Insert Material: |
| Plastic diallyl phthalate single mating end |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Anodize |
| Insert Material Specification: |
| |

Mil-m-14, type sdg-f military specification single material response single mating end



Shell Guide Type And Location Designator:

F slot

Unable To Decode:

Unable to decode and unable to decode

Thread Series Designator:

Unc and unc and unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.