NSN 5935-00-244-8201

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-244-8201

Body Style:

Straight shape

Overall Length:

Between 2.620 inches and 2.650 inches

Overall Height:

Between 0.990 inches and 1.140 inches

Overall Width:

Between 0.590 inches and 0.620 inches

Environmental Protection:

Moisture proof and shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.120 inches

Distance Between Mounting Facility Centers:

Between 2.401 inches and 2.411 inches

Mating End Quantity:

1

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Mating end

Shell Type:

Solid

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Tin

Insert Material Specification:

Mil-p-19833, ty gdi-30 military specification single material response single mating end

Included Contact Quantity:

35 single mating end single contact grouping

NSN 5935-00-244-8201

Electrical Receptacle Connector - Page 2 of 2



Inc	luded	Contact	Type
inc	luaea	Contact	туре

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.035 gold grains, troy and 0.035 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-p-19833 spec.