## NSN 5935-00-246-1008

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-246-1008

Body Style:
Single card
Overall Length:
3.855 inches
Overall Height:
0.633 inches
Overall Width:
0.248 inches
Unthreaded Mounting Hole Diameter:
0.187 inches
Distance Between Mounting Facility Centers:
3.565 inches
Board Accommodated Length:
2.900 inches single board
Board Accommodated Width:
0.070 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of independent contacts inserted board single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Pin single mating end single contact grouping
Contact Material Specification:
Qq-b-626 federal specification single material response single mating end single contact grouping
Insert Material Specification:
Mil-m-14 military specification single material response single mating end

Included Contact Quantity:

60 single mating end single contact grouping

## NSN 5935-00-246-1008

Electrical Receptacle Connector - Page 2 of 2



nd single contact grouping cation:

Contact surfaces gold

**Precious Material And Weight:** 

0.060 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.