

NSN 5935-00-246-1599 Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-00-246-1599 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.312 inches **Overall Diameter:** 0.625 inches **Environmental Protection:** Vibration resistant and shock resistant **Cable Entrance Diameter:**

Between 0.135 inches and 0.155 inches

Mounting Facility Thickness:

0.125 inches

Threaded Device Type:

Mounting bushing

Mating End Quantity:

Contact Position Arrangement Style:

Nonstd single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Polarization Method:

Key, multiple key groove

Insert Position In Deg:

90.0 and 180.0 and 270.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Connector Cable Strain Relief Method:

Compression nut

Thread Size:

0.476 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

NSN 5935-00-246-1599

Electrical Receptacle Connector - Page 2 of 2



| Insert Material: |
|---|
| Plastic polytetrafluoroethylene single mating end |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Contact Material Specification: |
| Qq-c-530 federal specification single material response single mating end single contact grouping |
| Shell Material: |
| Copper alloy |
| Shell Surface Treatment: |
| Nickel |
| Shell Surface Treatment Specification: |
| Qq-n-290, class 2 federal specification single treatment response |
| Shell Material Specification: |
| Qq-b-626, comp 1/2 hard federal specification single material response |
| Included Contact Quantity: |
| 1 single mating end single contact grouping |
| Bushing Accommodation Hole Shape: |
| Round |
| Included Contact Type: |
| Coaxial socket single mating end single contact grouping |
| Precious Material And Location: |
| Contact surface gold |
| Precious Material And Weight: |
| 0.001 gold grains, troy |
| Precious Material: |
| Gold |
| Thread Series Designator: |
| Unef |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| |