Electrical Receptacle Connector - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5935-00-246-2051

Thread Class:
Thread Pitch Diameters:
+1.355 to 1.375 inches
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Unable To Decode:
Unable to decode and unable to decode
Overall Length:
2.703 inches
Overall Height:
Between 1.719 inches and 1.750 inches
Overall Width:
Between 1.719 inches and 1.750 inches
Unthreaded Mounting Hole Diameter:
0.171 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.375 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.375 inches
Distance From Mounting Shoulder To Front Face:
1.005 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
7p single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
41.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0



Shell Type: Solid **Connector Locking Method:** Externally threaded shell **Thread Length:** 0.900 inches Thready Qty Per Inch (tpi): 4 Thread Size: 1.500 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold and silver single mating end single contact grouping **Insert Material:** Rubber single mating end **Terminal Type:** Crimp single mating end single contact grouping Shell Material: Aluminum alloy 6061 **Shell Surface Treatment:** Anodize **Shell Material Specification:** Qq-a-270, comp 6061, t6 federal specification single material response **Included Contact Quantity:** 7 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Special Features:** Contact designation 12-311, furnished items- protective cover **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.035 gold grains, troy and 0.035 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Special acme Shelf Life: N/a Unit Of Measure:

Electrical Receptacle Connector - Page 3 of 3

Demilitarization:

No

Fiig:

A039b0

