

View Online at <https://aerobasegroup.com/nsn/5935-00-246-8733>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, w/ or w/o cover

Overall Length:

4.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.375 inches

Overall Height:

5.625 inches

Overall Width:

5.000 inches

Environmental Protection:

Watertight

Unthreaded Mounting Hole Diameter:

0.281 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

3.000 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

4 single mating end

Contact Removability:

Removable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

60.0 single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

600.0 single mating end all contact groupings

Contact Maximum Dc Voltage Rating In Volts:

250.0 single mating end all contact groupings

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thready Qty Per Inch (tpi):

20

Thread Size:

2.250 inches

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Silver single mating end all contact groupings

Terminal Type:

Crimp single mating end all contact groupings

Shell Material:

Aluminum

Included Contact Quantity:

3 single mating end 2nd contact grouping

Included Contact Type:

Flat socket single mating end all contact groupings

Special Features:

Furnished items - hinged cover plate

Precious Material And Location:

Contact surfaces silver

Precious Material And Weight:

0.020 silver grains, troy

Precious Material:

Silver

Thread Series Designator:

Un

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0