NSN 5935-00-247-1489

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-247-1489 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling w/backshell **Overall Length:** 1.156 inches **Overall Diameter:** 0.562 inches **Environmental Protection:** Weatherproof **Distance From Mounting Shoulder To Front Face:** Between 0.246 inches and 0.252 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity:** 1 **Contact Position Arrangement Style:** C single mating end **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Bayonet latch Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.375 inches **Terminal Location:** Back single mating end single contact grouping **Insert Material:** Rubber synthetic single mating end **Terminal Type:** Turret single mating end single contact grouping **Shell Material:** Copper alloy

Silver

Shell Surface Treatment:

NSN 5935-00-247-1489

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:
1 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round w/flat
Included Contact Type:
Coaxial socket single mating end single contact grouping
Precious Material And Location:
Shell surface silver
Precious Material And Weight:
0.100 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A039b0