## NSN 5935-00-247-2120

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-247-2120

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
Between 1.035 inches and 1.100 inches
Overall Diameter:
Between 1.455 inches and 1.475 inches
Environmental Protection:
Moisture resistant and shock proof and vibration resistant and salt water resistant
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
18-09 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet latch
Thready Qty Per Inch (tpi):
28
Thread Size:
1.125 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Contact Surface Treatment Specification:
Mil-g-45204, type 1, class 1 military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping

## **NSN 5935-00-247-2120**Electrical Plug Connector - Page 2 of 2



Shell Material:	
Aluminum alloy 6061	
Shell Surface Treatment:	
Cadmium	
Shell Surface Treatment Specification:	
Qq-p-416, type 2, cl 3 federal specification single treatment response	
Shell Material Specification:	
Qq-a-367, t6 federal specification single material response	
Included Contact Quantity:	
9 single mating end single contact grouping	
Included Contact Type:	
Round pin single mating end single contact grouping	
Precious Material And Location:	
Contact surfaces gold	
Precious Material:	
Gold	
Test Data Document:	
81349-mil-c-81511 specification (includes engineering type bulletins, brochures, etc., that reflect specification ty	pe data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general ty	pe data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc	c.).
Thread Series Designator:	
Un	
Specification Data:	
81349-mil-c-81511 government specification	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	
Mil-std (military Standard):	
Mil-g-45204 spec.	