

View Online at <https://aerobasegroup.com/nsn/5935-00-247-5385>

**Body Style:**

Straight type

**Overall Length:**

Between 3.499 inches and 3.511 inches

**Overall Height:**

0.620 inches

**Overall Width:**

0.248 inches

**Environmental Protection:**

Vibration resistant and thermal shock resistant and corrosion resistant and shock resistant and moisture resistant

**Unthreaded Mounting Hole Diameter:**

0.098 inches

**Distance Between Mounting Facility Centers:**

3.210 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

**Polarization Method:**

Mating end and contact

**Connector Locking Method:**

Friction

**Operating Temperature Rating:**

Between -65.0 degrees celsius and 125.0 degrees celsius

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Plastic single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd treatment response single mating end single contact grouping

**Criticality Code Justification:**

Feat

**Terminal Type:**

Solder well single mating end single contact grouping

**Contact Material Specification:**

Qq-c-533 federal specification single material response single mating end single contact grouping

**Insert Material Specification:**

Mil-m-14f military specification single material response single mating end

**Included Contact Quantity:**

68 single mating end single contact grouping

**Included Contact Type:**

Square socket single mating end single contact grouping

**Special Features:**

Connector keyed at position 4 and 32

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.068 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.