Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-247-9107

## Thread Class:

2a and 2b and 2a

## **Thread Direction:**

Right-hand and right-hand and right-hand

## **Body Style:**

Straight shape

## **Overall Length:**

1.688 inches

#### **Overall Height:**

0.531 inches

**Overall Width:** 

#### 0.344 inches

**Distance Between Mounting Facility Centers:** 

1.562 inches

#### **Threaded Device Type:**

Coupling facility and mounting stud

# Mating End Quantity:

1

## **Contact Position Arrangement Style:**

20 20-20 single mating end

## **Contact Removability:**

Nonremovable single mating end single contact grouping

## **Contact Maximum Current Rating In Amps:**

7.5 single mating end single contact grouping

## Contact Maximum Ac Voltage Rating In Volts:

1950.0 single mating end single contact grouping

#### **Polarization Method:**

Jackscrew

## **Connector Locking Method:**

Jackscrew-socket

#### **End Application:**

Aircraft, phantom f-4

#### Thready Qty Per Inch (tpi):

32 and 32 and 40

#### **Thread Size:**

0.138 inches and 0.138 inches and 0.112 inches

## **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping



Insert Material:
Plastic single mating end
Criticality Code Justification:
Feat
Terminal Type:
Solder well single mating end single contact grouping
Included Contact Quantity:
20 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Special Features:
Weapon system essential
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.020 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc and unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0