

View Online at <https://aerobasegroup.com/nsn/5935-00-250-2364>

Body Style:

Straight shape, flush mount

Overall Length:

Between 1.297 inches and 1.357 inches

Overall Height:

Between 3.094 inches and 3.124 inches

Overall Width:

Between 1.985 inches and 2.015 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

2.783 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.437 inches

Mating End Quantity:

2

Contact Position Arrangement Style:

57 all mating ends

Contact Removability:

Nonremovable all mating ends all contact groupings

Contact Maximum Current Rating In Amps:

7.5 all mating ends all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

500.0 all mating ends all contact groupings

Shell Type:

Solid

Terminal Location:

Back all mating ends all contact groupings

Contact Material:

Copper alloy all mating ends all contact groupings

Contact Surface Treatment:

Gold all mating ends all contact groupings

Insert Material:

Plastic phenolic all mating ends

Contact Surface Treatment Specification:

Mil-g-45204, type 2, class 1 military specification single treatment response all mating ends all contact groupings

Terminal Type:

Solder well all mating ends all contact groupings

Shell Material:

Aluminum alloy a380.0

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Shell Material Specification:

Qq-a-591 federal specification single material response

Insert Material Specification:

Mil-m-14 military specification single material response all mating ends

Included Contact Type:

Round socket all mating ends all contact groupings

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.114 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.