## NSN 5935-00-250-2992

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-250-2992

**Body Style:** 

Straight shape, internal coupling

**Overall Diameter:** 

1.305 inches

**Environmental Protection:** 

Moisture resistant and salt water resistant and vibration resistant

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

16-23 single mating end

**Contact Removability:** 

Removable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:** 

7.5 single mating end 2nd contact grouping

**Polarization Method:** 

Keyway or multiple keyway

**Insert Position In Deg:** 

0.0

**Shell Type:** 

Potting

**Connector Locking Method:** 

Bayonet latch

**Connector Cable Strain Relief Method:** 

Potting type

**Terminal Location:** 

Back single mating end all contact groupings

**Contact Material:** 

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:** 

Gold single mating end all contact groupings

**Insert Material:** 

Plastic single mating end

**Terminal Type:** 

Crimp single mating end all contact groupings

**Shell Material:** 

Aluminum alloy

**Included Contact Quantity:** 

22 single mating end 2nd contact grouping

**Included Contact Type:** 

Round socket single mating end all contact groupings

**Precious Material And Location:** 

Contact surfaces gold

## NSN 5935-00-250-2992

Electrical Plug Connector - Page 2 of 2



	Precious	Materia	I And \	Weight	t:
--	----------	---------	---------	--------	----

0.023 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0