# NSN 5935-00-250-7820

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-250-7820 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Rectangular shape **Overall Length:** 2.000 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 1.700 inches **Overall Height:** 1.080 inches **Overall Width:** 1.100 inches **Environmental Protection:** Moisture resistant and shock resistant and vibration resistant and corrosion resistant and thermal shock resistant **Unthreaded Mounting Hole Diameter:** 0.120 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.800 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Polarization boss **Connector Locking Method:** Jackscrew Thready Qty Per Inch (tpi): **Thread Size:** 0.138 inches

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:** 

Glass fiber single mating end and plastic diallyl phthalate single mating end

# NSN 5935-00-250-7820

Electrical Receptacle Connector - Page 2 of 2



# **Contact Surface Treatment Specification:**

Mil-g-45204, type 1, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 1 federal specification 2nd treatment response single mating end single contact grouping

# **Terminal Type:**

Crimp single mating end single contact grouping

# **Contact Material Specification:**

Qq-c-533 federal specification single material response single mating end single contact grouping

### **Insert Material Specification:**

Mil-m-14, ty sdg-f military specification all material responses single mating end

# **Included Contact Quantity:**

50 single mating end single contact grouping

### **Included Contact Type:**

Square socket single mating end single contact grouping

# **Precious Material And Location:**

Contact surfaces gold

# **Precious Material And Weight:**

0.050 gold grains, troy

**Precious Material:** 

Gold

### **Thread Series Designator:**

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

### Mil-std (military Standard):

Mil-g-45204 spec.