Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-250-8908

Thread Class:
2a
Thread Direction:
Right-hand
Overall Length:
0.343 inches
Overall Diameter:
0.562 inches
Threaded Device Type:
Mounting bushing
Mating End Quantity:
1
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
300.0 single mating end single contact grouping
Polarization Method:
Contact
Connector Locking Method:
Bayonet shell
Thread Length:
0.250 inches
Thread Size:
0.500 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic melamine single mating end
Terminal Type:
Solder well single mating end single contact grouping
Insert Material Specification:
Mil-m-14, mme military specification single material response single mating end
Included Contact Quantity:
5 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round keyed



Included Contact Type:

Round socket single mating end single contact grouping

Color: Natural

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.