NSN 5935-00-251-3179

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-251-3179

Body Style:
Straight shape
Overall Length:
3.219 inches
Overall Height:
1.000 inches
Overall Width:
Between 1.215 inches and 1.275 inches
Environmental Protection:
Vibration resistant
Unthreaded Mounting Hole Diameter:
Between 0.123 inches and 0.127 inches
Distance Between Mounting Facility Centers:
Between 2.870 inches and 2.880 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
24 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
800.0 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Connector Locking Method:
Latch
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy 766 single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, class 2 military specification single treatment response single mating end single contact grouping
Terminal Type:
Tab, solder lug single mating end single contact grouping

NSN 5935-00-251-3179

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Copper alloy
Shell Surface Treatment:
Nickel
Shell Material Specification:
Qq-b-613, comp 4, annealed federal specification single material response
Insert Material Specification:
Mil-m-14, type mdg military specification single material response single mating end
Included Contact Quantity:
24 single mating end single contact grouping
Included Contact Type:
Flat pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.024 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.