

View Online at <https://aerobasegroup.com/nsn/5935-00-251-7351>

**Thread Class:**

2a and 2a

**Thread Direction:**

Right-hand and right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

2.438 inches

**Overall Height:**

2.750 inches

**Overall Width:**

2.750 inches

**Unthreaded Mounting Hole Diameter:**

0.173 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

2.188 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

2.188 inches

**Distance From Mounting Shoulder To Front Face:**

0.875 inches

**Threaded Device Type:**

Coupling facility and hub

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

40-9 single mating end

**Contact Removability:**

Removable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:**

73.0 single mating end 1st contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 single mating end all contact groupings

**Contact Maximum Dc Voltage Rating In Volts:**

700.0 single mating end all contact groupings

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Detent

**Thready Qty Per Inch (tpi):**

16 and 16

**Thread Size:**

2.500 inches and 2.250 inches

**Terminal Location:**

Back single mating end all contact groupings

**Terminal Type:**

Solder well single mating end all contact groupings

**Shell Material:**

Aluminum alloy

**Included Contact Quantity:**

24 single mating end 3rd contact grouping

**Included Contact Type:**

Round pin single mating end all contact groupings

**Thread Series Designator:**

Un and un

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0