Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-251-7351

Thread C	Class:
2a and 2a	a
Thread D	Direction:
Right-har	nd and right-hand
Body Sty	yle:
Straight s	shape, external coupling
Overall L	_ength:
2.438 inc	hes
Overall H	leight:
2.750 inc	hes
Overall V	Nidth:
2.750 inc	hes
Unthread	ded Mounting Hole Diameter:
0.173 inc	hes
Center T	o Center Distance Between Mounting Facilities Parallel To Height:
2.188 inc	hes
Distance	e Between Centerlines Of Mounting Facilities Parallel To Body Width:
2.188 inc	hes
Distance	e From Mounting Shoulder To Front Face:
0.875 inc	hes
Threade	d Device Type:
Coupling	facility and hub
Mating E	End Quantity:
1	
Contact	Position Arrangement Style:
40-9 sing	gle mating end
Contact	Removability:
Removat	ble single mating end all contact groupings
Contact	Maximum Current Rating In Amps:
73.0 sing	le mating end 1st contact grouping
Contact	Maximum Ac Voltage Rating In Volts:
500.0 sin	gle mating end all contact groupings
Contact	Maximum Dc Voltage Rating In Volts:
700.0 sin	gle mating end all contact groupings
Polarizat	tion Method:
Keyway o	or multiple keyway
Insert Po	osition In Deg:
0.0	
Shell Ty	pe:
Solid	
Connect	or Locking Method:
Detent	



Thready Qty Per Inch (tpi):

16 and 16

# Thread Size:

2.500 inches and 2.250 inches

# **Terminal Location:**

Back single mating end all contact groupings

# **Terminal Type:**

Solder well single mating end all contact groupings

### Shell Material:

Aluminum alloy

# **Included Contact Quantity:**

24 single mating end 3rd contact grouping

## Included Contact Type:

Round pin single mating end all contact groupings

## **Thread Series Designator:**

Un and un

Shelf Life:

N/a

## Unit Of Measure:

Demilitarization:

No

---

Fiig:

A039b0