

View Online at <https://aerobasegroup.com/nsn/5935-00-251-8906>

Body Style:

Right angle type

Overall Length:

3.050 inches

Overall Width:

0.250 inches

Body Height:

0.335 inches

Environmental Protection:

Thermal shock resistant and vibration resistant and moisture resistant

Unthreaded Mounting Hole Diameter:

0.120 inches

Distance Between Mounting Facility Centers:

2.800 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204, type 1, grade c, class 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

44 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

Guide pin/socket 0.050 in. Height; jackscrew type-female and location-right hand and jackscrew type-male and location-left hand

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.044 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.