## NSN 5935-00-252-6774



Electrical Receptacle Connector Body - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-00-252-6774 **Thread Class:** 2a and 2b and 2a **Thread Direction:** Right-hand and right-hand and right-hand **Body Style:** Rectangular shape **Overall Length:** 2.719 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 1.969 inches **Overall Height:** 0.656 inches **Overall Width:** 1.125 inches **Environmental Protection:** Shock proof and vibration proof **Unthreaded Mounting Hole Diameter:** 0.125 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.500 inches **Threaded Device Type:** Coupling facility and mounting stud **Mating End Quantity: Contact Position Arrangement Style:** 75 single mating end **Polarization Method:** Jackscrew and shell Shell Type: Solid **Connector Locking Method:** Jackscrew-socket Thready Qty Per Inch (tpi): 32 and 32 and 40 **Thread Size:** 0.138 inches and 0.138 inches and 0.112 inches **Insert Material:** Plastic diallyl phthalate single mating end **Shell Material:** 

Passivate

Aluminum alloy

**Shell Surface Treatment:** 

## NSN 5935-00-252-6774

Electrical Receptacle Connector Body - Page 2 of 2



Shell Guide Type And Location Designator:
B slot
Thread Series Designator:
Unc and unc and unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0