NSN 5935-00-252-6799

Electrical Receptacle Connector Body - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-252-6799

| Thread Class: | | | | | |
|--|--|--|--|--|--|
| 2a and 2b and 2a | | | | | |
| Thread Direction: | | | | | |
| Right-hand and right-hand | | | | | |
| Body Style: | | | | | |
| Straight shape | | | | | |
| Overall Length: | | | | | |
| 1.250 inches | | | | | |
| Overall Height: | | | | | |
| 0.656 inches | | | | | |
| Overall Width: | | | | | |
| 0.438 inches | | | | | |
| Environmental Protection: | | | | | |
| Shock proof and vibration proof | | | | | |
| Unthreaded Mounting Hole Diameter: | | | | | |
| 0.125 inches | | | | | |
| Distance Between Mounting Facility Centers: | | | | | |
| 0.937 inches | | | | | |
| Threaded Device Type: | | | | | |
| Coupling facility and mounting stud | | | | | |
| Mating End Quantity: | | | | | |
| 1 | | | | | |
| Contact Position Arrangement Style: | | | | | |
| 14 single mating end | | | | | |
| Polarization Method: | | | | | |
| Jackscrew and shell | | | | | |
| Shell Type: | | | | | |
| Solid | | | | | |
| Connector Locking Method: | | | | | |
| Jackscrew-socket | | | | | |
| Thready Qty Per Inch (tpi): | | | | | |
| 32 and 32 and 40 | | | | | |
| Thread Size: | | | | | |
| 0.138 inches and 0.138 inches and 0.112 inches | | | | | |
| Insert Material: | | | | | |
| Plastic diallyl phthalate single mating end | | | | | |
| Shell Material: | | | | | |
| Aluminum alloy | | | | | |
| Shell Surface Treatment: | | | | | |
| Passivate | | | | | |
| Shell Guide Type And Location Designator: | | | | | |
| B slot | | | | | |

NSN 5935-00-252-6799

Electrical Receptacle Connector Body - Page 2 of 2



| T | 'nr | ead | Series | Design | nator: |
|---|-----|-----|---------------|--------|--------|
| | | | | | |

Unc and unc and unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0