

View Online at <https://aerobasegroup.com/nsn/5935-00-254-1124>

Thread Direction:

Right-hand

Body Style:

Hood, side opening w/clamp

Overall Length:

2.685 inches

Overall Height:

2.125 inches

Overall Width:

1.035 inches

Cable Entrance Diameter:

0.473 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of independent contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

500.0 single mating end single contact grouping

Polarization Method:

Mating end

Shell Type:

Hood, side opening

Connector Locking Method:

Latch

Connector Cable Strain Relief Method:

Cable clamp

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

Terminal Type:

Tab, solder lug single mating end single contact grouping

Shell Surface Treatment:

Zinc and chromate

Insert Material Specification:

Mil-m-14, ty mdg military specification single material response single mating end

Included Contact Quantity:

36 single mating end single contact grouping

Included Contact Type:

Leaf spring single mating end single contact grouping

Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.036 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.