Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-254-3437

view Online at https://aerobasegroup.com/nsi//3505-00-254-5457
Body Style:
Wall type
Overall Height:
1.218 inches
Overall Width:
1.718 inches
Distance Between Mounting Facility Centers:
3.281 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
3 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
30.0 single mating end all contact groupings
Contact Maximum Ac Voltage Rating In Volts:
250.0 single mating end all contact groupings
Contact Maximum Dc Voltage Rating In Volts:
250.0 single mating end all contact groupings
Connector Locking Method:
Contact twistlock
Terminal Location:
Side single mating end all contact groupings
Contact Material:
Copper alloy single mating end all contact groupings
Contact Surface Treatment:
Nickel single mating end all contact groupings
Insert Material:
Plastic phenolic single mating end
Terminal Type:
Screw w/wire lock single mating end all contact groupings
Insert Material Specification:
Mil-m-14, type cfg military specification single material response single mating end
Included Contact Quantity:
2 single mating end 2nd contact grouping
Included Contact Type:
U-socket single mating end 2nd contact grouping
Shelf Life:
N/a
Unit Of Measure:

---

Electrical Receptacle Connector - Page 2 of 2



Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.