NSN 5935-00-255-3660

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-255-3660 **Body Style:** Right angle type **Overall Length:** 4.594 inches **Overall Height:** 0.719 inches **Overall Width:** 0.600 inches **Environmental Protection:** Heat resistant and humidity resistant and corrosion resistant and shock resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.156 inches **Distance Between Mounting Facility Centers:** 4.250 inches **Mating End Quantity: Contact Position Arrangement Style:** 35 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 1575.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 2175.0 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Connector Locking Method: Terminal Location:** Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Pin single mating end single contact grouping

NSN 5935-00-255-3660

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and iridium
Shell Surface Treatment Specification:
Qq-p-416 federal specification 1st treatment response
Shell Material Specification:
Qq-a-591 federal specification single material response
Insert Material Specification:
Mil-m-14, ty mdg military specification single material response single mating end
Shell Guide Type And Location Designator:
H pin
Included Contact Quantity:
35 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.035 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-m-14 spec.