

View Online at <https://aerobasegroup.com/nsn/5935-00-255-3671>

**Thread Class:**

2a and 2b

**Thread Direction:**

Right-hand and right-hand

**Overall Length:**

0.750 inches

**Overall Height:**

0.508 inches

**Overall Diameter:**

0.562 inches

**Environmental Protection:**

Vibration resistant and shock resistant and thermal shock resistant and corrosion resistant and moisture resistant

**Threaded Device Type:**

Coupling facility and mounting hole

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Sma single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 single mating end single contact grouping

**Thready Qty Per Inch (tpi):**

36 and 56

**Thread Size:**

0.250 inches and 0.086 inches

**Terminal Location:**

Side single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic tetrafluoroethylene single mating end

**Terminal Type:**

Screw single mating end single contact grouping

**Shell Material:**

Stainless steel

**Included Contact Quantity:**

1 single mating end single contact grouping

**Included Contact Type:**

Coaxial socket single mating end single contact grouping

**Precious Material And Location:**

Contact surface gold

**Precious Material And Weight:**

0.005 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Uns and unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0