

View Online at https://aerobasegroup.com/nsn/5935-00-255-3687

Thread	Class:
2a and 2b	

**Thread Direction:** 

Right-hand

# Body Style:

Straight shape

## **Overall Length:**

1.250 inches

#### **Overall Height:**

0.609 inches

**Overall Width:** 

#### 0.578 inches

**Distance Between Mounting Facility Centers:** 

1.000 inches

#### **Threaded Device Type:**

Coupling facility and mounting stud

## Mating End Quantity:

1

### **Contact Position Arrangement Style:**

26 single mating end

## **Contact Removability:**

Removable single mating end single contact grouping

### Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

### Contact Maximum Ac Voltage Rating In Volts:

1400.0 single mating end single contact grouping

### **Connector Locking Method:**

Externally threaded shell

# Thread Size:

0.086 inches

### **Terminal Location:**

Back single mating end single contact grouping

### **Contact Material:**

Copper alloy single mating end single contact grouping

### **Contact Surface Treatment:**

Gold single mating end single contact grouping

#### **Insert Material:**

Plastic single mating end

#### **Terminal Type:**

Crimp single mating end single contact grouping

# **Insert Material Specification:**

Mil-m-14, type sdg-f military specification single material response single mating end



**Included Contact Quantity:** 26 single mating end single contact grouping Included Contact Type: Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.026 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0 Mil-std (military Standard): Mil-m-14 spec.