NSN 5935-00-255-6196

2a

Thread Direction:

Right-hand

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-255-6196

Thread Class:

Body Style:
Straight shape, latching
Overall Length:
0.530 inches
Bushing Diameter:
0.375 inches
Overall Width:
0.500 inches
Diameter:
0.500 inches
Threaded Device Type:
Mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
4 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Polarization Method:
Contact
Thread Length:
0.237 inches
Thready Qty Per Inch (tpi):
24
Thread Size:
0.375 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Plastic melamine single mating end

NSN 5935-00-255-6196

Fiig: A039b0

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Solder well single mating end single contact grouping
Included Contact Quantity:
4 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Round socket single mating end single contact grouping
Special Features:
Non-latching; large contact in position a for polarization; notch 0.073 in. Deep next to contact position a
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.020 gold grains, troy and 0.020 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No