

View Online at <https://aerobasegroup.com/nsn/5935-00-256-3410>

Body Style:

Straight shape, internal coupling

Overall Length:

3.420 inches

Overall Diameter:

1.391 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof

Mating End Quantity:

2

Contact Position Arrangement Style:

19p 1st mating end

Contact Removability:

Removable all mating ends all contact groupings

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet latch

Contact Surface Treatment:

Gold all mating ends all contact groupings and nickel all mating ends all contact groupings

Contact Surface Treatment Specification:

Mil-g-45204 type 1, cl 1, grade c military specification 1st treatment response all mating ends all contact groupings and qq-n-290 grade e federal specification 2nd treatment response all mating ends all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416 type 2, cl 3 federal specification single treatment response

Shell Material Specification:

Qq-a-591 federal specification single material response

Included Contact Quantity:

32 2nd mating end single contact grouping

Included Contact Type:

Round socket 2nd mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.051 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.