## NSN 5935-00-256-8755

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-256-8755

**Body Style:** Straight edge type w/mounting flange **Overall Length:** 3.190 inches **Overall Height:** 0.663 inches **Overall Width:** 0.340 inches **Unthreaded Mounting Hole Diameter:** 0.142 inches **Distance Between Mounting Facility Centers:** 2.940 inches **Board Accommodated Length:** 2.500 inches single board **Board Accommodated Width:** Between 0.054 inches and 0.070 inches **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 1 row of contacts inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Contact to contact polarizing keys **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic phenolic single mating end and glass single mating end **Contact Surface Treatment Specification:** Mil-g-45204, type 2, class 1 military specification single treatment response single mating end single contact grouping **Terminal Type:** Wire wrap single mating end single contact grouping

**Included Contact Quantity:** 

15 single mating end single contact grouping

**Included Contact Type:** 

Bifurcated spring single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

## NSN 5935-00-256-8755

Electrical Receptacle Connector - Page 2 of 2



| <b>Precious Material And Weight:</b> |
|--------------------------------------|
| 0.015 gold grains, troy              |
| Precious Material:                   |
| Gold                                 |
| Shelf Life:                          |
| N/a                                  |
| Unit Of Measure:                     |
|                                      |
| Demilitarization:                    |
| No                                   |
| Fiig:                                |
| A039b0                               |

Mil-std (military Standard):

Mil-g-45204 spec.