Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-256-9760

Thread Class:
2a
Za Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
Between 1.275 inches and 1.340 inches
Overall Height:
Between 0.929 inches and 0.945 inches
Overall Width:
Between 0.929 inches and 0.945 inches
Environmental Protection:
Pressure proof and moisture proof and vibration resistant
Unthreaded Mounting Hole Diameter:
Between 0.116 inches and 0.126 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 0.714 inches and 0.724 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 0.714 inches and 0.724 inches
Distance From Mounting Shoulder To Front Face:
Between 0.765 inches and 0.775 inches
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
"10-5, 10-05" single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
95.0 and 145.0 and 220.0 and 255.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Thready Qty Per Inch (tpi):
28
Thread Size:
0.625 inches



specification

<b>-</b>
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Contact Surface Treatment Specification:
Mil-g-45204, type 1, class 2 military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy 6061
Shell Surface Treatment:
Chromium
Shell Surface Treatment Specification:
Qq-a-367, comp 6061, t6 federal specification single treatment response
Included Contact Quantity:
5 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.025 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-81511 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Un
Specification Data:
81349-mil-c-81511/1 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):

Mil-g-45204 spec.