# NSN 5935-00-256-9764

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-256-9764 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** Between 1.275 inches and 1.340 inches **Overall Height:** Between 1.117 inches and 1.133 inches **Overall Width:** Between 1.117 inches and 1.133 inches **Environmental Protection:** Pressure proof and moisture proof and vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.116 inches and 0.126 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.901 inches and 0.911 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.901 inches and 0.911 inches **Distance From Mounting Shoulder To Front Face:** Between 0.765 inches and 0.775 inches **Threaded Device Type:** Back shell **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 14-19 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 40.0 and 112.0 and 228.0 and 258.0 **Shell Type:** Solid **Connector Locking Method:** Bayonet pin Thready Qty Per Inch (tpi):

28

**Thread Size:** 

0.875 inches

# NSN 5935-00-256-9764

Electrical Receptacle Connector - Page 2 of 2



_			
Torn	nina		ocation:
	ııııa	_	ocalion.

Back single mating end single contact grouping

### **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping

### **Contact Surface Treatment Specification:**

Mil-g-45204, type 1, class 2 military specification single treatment response single mating end single contact grouping

### **Terminal Type:**

Crimp single mating end single contact grouping

### **Shell Material:**

Aluminum alloy 6061

### **Shell Surface Treatment:**

Chromium

### **Shell Surface Treatment Specification:**

Qq-a-367, comp 6061, t6 federal specification single treatment response

### **Included Contact Quantity:**

19 single mating end single contact grouping

### **Included Contact Type:**

Round socket single mating end single contact grouping

### **Precious Material And Location:**

Contact surfaces gold

# **Precious Material And Weight:**

0.019 gold grains, troy

### **Precious Material:**

Gold

### **Test Data Document:**

81349-mil-c-81511 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Thread Series Designator:**

Un

# **Specification Data:**

81349-mil-c-81511/1 government specification

# Shelf Life:

N/a

### **Unit Of Measure:**

# **Demilitarization:**

No

# Fiig:

A039b0

### Mil-std (military Standard):

Mil-g-45204 spec.