Electrical Plug Connector - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5935-00-257-6704

Thread Class:
2a and 2b
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape, internal coupling w/backshell
Overall Length:
Between 1.808 inches and 1.878 inches
Overall Diameter:
1.250 inches
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
Nonstd single mating end
Contact Removability:
Nonremovable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
41.0 single mating end all contact groupings
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end all contact groupings
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end all contact groupings
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling nut
Thready Qty Per Inch (tpi):
20 and 20
Thread Size:
0.875 inches and 1.000 inches
Terminal Location:
Back single mating end all contact groupings
Contact Material:
Nickel alloy single mating end 2nd contact grouping
Insert Material:
Rubber single mating end

## NSN 5935-00-257-6704 Electrical Plug Connector - Page 2 of 2



Terminal Type:
Solder well single mating end all contact groupings
Shell Material:
Aluminum alloy 6061 or aluminum alloy 2011
Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416, type ii, class 3 federal specification all treatment responses
Shell Material Specification:
Qq-a-225 federal specification 1st material response or qq-a-225 federal specification 2nd material response
Included Contact Quantity:
1 single mating end 2nd contact grouping
Included Contact Type:
Round socket single mating end all contact groupings
Thread Series Designator:
Unef and unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0